P4150L

Lined Double Ply Neoprene Coated Glass Fibre Ducting - *Light Weight*

specialistductingsupplies



Construction: Double ply construction with an outer layer of neoprene coated glass fibre fabric and an inner layer of neoprene coated fibreglass. The spring steel helix is encapsulated between the 2 plies with a double outer neoprene coated glass fibre retention cord.

Colour: Black with white cord.

Standard Length: 4 metres.

Temperature Range: -45°C to +150°C in a 20°C ambient.

Applications: Conveying hot or cold air, fumes, light powders and dust at low pressure.

Properties: Flexible, lightweight and a smooth bore.

Options: P4150 – Single Ply.
Available with EPDM/Nitrile Liners or polyester fabric.
Wire free cuff.

Diameter mm	Weight Kg/m	Bend Radius mm	Max. Work. Press. Bar	Max. Vacuum Bar
25	0.15	14	1.95	0.50
38	0.20	20	1.65	0.40
51	0.30	25	1.65	0.40
63	0.36	30	1.40	0.35
76	0.46	34	1.40	0.35
83	0.51	35	1.30	0.30
89	0.53	36	1.20	0.25
102	0.60	38	1.00	0.20
127	0.85	41	0.70	0.20
152	1.10	55	0.55	0.15
160	1.18	60	0.55	0.15
178	1.28	65	0.45	0.10
203	1.43	80	0.35	0.06
254	2.06	110	0.20	0.04
305	2.47	120	0.20	0.03

Technical data at +20°C. Other diameters/lengths available upon request.

ISO 9001:2015 Quality Management

Specialist Ducting Supplies Limited | Craven House | Steeton Grove | Steeton | Keighley | West Yorkshire | BD20 6TT

t | 01535 656 656 f | 01535 656 321 e | info@sdslimited.co.uk **www.sdslimited.co.uk**