PU 200

Polyurethane Ducting - *Medium Weight*

specialistductingsupplies



Construction: Polyester-Polyurethane encapsulating a blue PVC coated spring steel wire helix.

Colour: Clear.

Standard Length: 10 metres.

Temperature Range: -40°C to +100°C in a 20°C ambient.

Applications: Suction and transportation of sawdust and wood splinters, cereals, granulates, abrasives, solids and fumes in the woodworking and pharmaceutical industries.

Properties: Excellent flexibility, good abrasion resistance and compressability. Good resistance to oil and petrol fumes.

Options: Various diameters & lengths available upon request.

Diameter mm	Weight Kg/m	Wall Thickness mm	Bend Radius mm	Max. Work. Press. Bar	Max. Vacuum Bar
38	0.20	0.4	30	0.60	0.19
45	0.22	0.4	40	0.55	0.18
51	0.26	0.4	45	0.50	0.16
63	0.28	0.4	50	0.50	0.14
76	0.32	0.4	60	0.45	0.14
82	0.34	0.4	62	0.40	0.13
89	0.38	0.4	70	0.40	0.13
102	0.64	0.4	75	0.35	0.12
115	0.69	0.4	85	0.30	0.11
127	0.80	0.4	95	0.30	0.10
140	0.88	0.4	105	0.25	0.09
152	0.96	0.4	115	0.21	0.09
160	1.01	0.4	120	0.20	0.09
178	1.12	0.4	135	0.20	0.08
203	1.26	0.4	155	0.17	0.08
228	1.45	0.4	175	0.15	0.07
254	1.60	0.4	195	0.12	0.06
279	1.73	0.4	210	0.12	0.06
305	1.92	0.4	230	0.10	0.05

Technical data at +20°C. Other diameters/lengths available upon request.

ISO 9001:2015 Quality Management

Specialist Ducting Supplies Limited | Craven House | Steeton Grove | Steeton | Keighley | West Yorkshire | BD20 6TT

t | 01535 656 656 f | 01535 656 321 e | info@sdslimited.co.uk **www.sdslimited.co.uk**